

KVASH/NINA Ye. I.

Category : USSR/Solid State Physics - Phase Transformation in
Solid Bodies

E-5

Abs Jour : Ref Zhur - Fizika, No 5, 1957, No 6655

Author : Frosvirin, V.I., Kvashina, Ye.I.

Title : Effect of Alloying Elements on the Temper Brittleness of
Structural Steels;

Orig Pub : Tern. obrabotka i svoystva litoy stali. M., Mashgiz, 1955,
69-87

Abstract : It was established that addition of molybdenum up to 0.5% prevents the development of processes that cause the temper brittleness of structural chrome-nickel-molybdenum and chrome-manganese-molybdenum steels. Greater additions of molybdenum (1% and above) do not effect the temper brittleness. Addition of tungsten up to a definite limit (up to 1.6% for the 35 KhGV steel) retard strongly the development of the temper brittleness of structural steels. X-ray diffraction, carbide, and metallographic investigation methods, as well as measurements of the internal friction and other properties have shown that molybdenum and tungsten, which enter into

Card : 1/2

KVASHINA, Ye. I.

USSR/Solid State Physics - Phase Transformations in Solids, E-5

Abst Journal: Referat Zhur - Fizika, No 12, 1956, 34678

Author: Kvashina, Ye. I., Bondarenko, Ya. A.

Institution: None

Title: Experience in Electron-Microscopic Investigation of Austenitic Steel EI 257

Original Periodical: Metallovedeniye i obrabotka metallov, 1955, No 1, 34-36

Abstract: None

Cent. Sci Res Inst. Heavy Machine Building

1 of 1

- 1 -

14146 Internal Friction of Steel and Temper Brittleness.
E. I. Kvashina and V. I. Frovirin. Henry Bratcher Transla- 62
tion 14146, 3000, 0 p. (From: Izvestiya Akademii Nauk SSSR,
1955, no. 1, Jan., p. 157-158.) Henry Bratcher, Alhadena, Calif. MG
Previously abstracted from original. See item 10603, v. 4, 1)
Aug. 1955.

KVASHNINA, E. I.

USSR/ Engineering - Structural tests

Card 1/1 Rub. 128 - 14/23

Authors : Prosvirin, V. I., and Kvashnina, E. I.

Title : The effect of carbide forming elements on the brittleness of tempered steel.

Periodical : Vest. mash. 2, 58 - 67, Feb 1955

Abstract : The influence of manganese, molybdenum, tungsten and titanium admixtures on the brittleness of tempered steels at various temperatures, was investigated. Technical data are presented on testing temperatures, types of steel and admixtures used, and the chemical composition of various grade steels. Ten references: 2 German (1933 and 1942); 1 French (1946); 2 USA (1920 and 1950). Tables; graphs; illustrations.

Institution:

Submitted:

KVASHNINA, Ye. I.

Category : USSR/Solid State Physics - Mechanical properties of crystals and poly-crystalline compounds E-9

Abs Jour : Ref Zhur - Fizika, No 1, 1957 No 1368

Author : Prosvirin, V.I., Kvashnina, Ye.I.

Title : Position of the Cold-Shortness Threshold in the Tempering Brittleness

Orig Pub : Metallovedeniye i obrabotka metallov, 1955, No 3, 17-20

Abstract : When tempering beittleness is produced in steel, one observes a shift in the threshold of the cold-shortness towards high temperatures. Prolonging the heating time in high-temperature tempering shifts the cold-shortness threshold towards the lower temperatures, and increasing the grain dimension shifts it towards higher temperatures. No shift in the cold-shortness threshold is observed in stages that are not prone to tempering brittleness.

Cent. Sci. Res. Inst. Technology and Machine Building

Card : 1/1

KVASHNINA, Ye. I.
 Category : USSR/Solid State Physics - Phase transformation of solid bodies

E-5

Abs Jour : Ref Zhur - Fizika, No 1, 1957, No 1183

Author : Kvashnina, Ye. I.

Inst : TsNIITMASH, (Centr. Sci. Res. Inst. for Tech. Machinery), USSR

Title : Study of Intragranular Mosaic Structure of Austenite with the Aid of the Electron Microscope

Orig Pub : Metallovedeniye i obrabotka metallov, 1955, No 5, 15-17

Abstract : Report on the results of electron-microscopical investigations of the grain structure of the austenite of three brands of steel: 1KhN9T, EI402, EI448. The specimens were hardened from 1150°C. Each grain of austenite has its own orientation of blocks, the size of which differs in the different grains. Sections with a different block orientation are encountered inside the individual grains of austenite. Located around the grain boundaries is a small zone with a distinct distribution of blocks compared with the more remote zones of the grains.

Card : 1/1

KVASHNINA, Y. I.

SL-
LAPTOP

Study of the intragranular mosaic structure of austenite by use of the electron microscope. R. I. Kvashnina. *Metallurg. i Obrabotka Metallov* 1955, No. 5, 15-17. — The compons. of the 3 steels studied were: 1Kh18N9T, 0.11% C, 1.23 Mn, 0.48 Si, 10.68 Ni, 17.91 Cr, 0.6 Ti; E1402, 0.08 C, 1.0 Mn, 0.0 Si, 11.3 Ni, 18.3 Cr, 1.2 Nb; E1448, 0.03 C, 1.1 Mn, 0.8 Si, 11.2 Ni, 17.7 Cr, 2.45 Mo, 0.45 Ti. The steels were quenched from 1150°, polished, and repeatedly electrolytically etched with 10% ammonium persulfate at 0.2 amp./sq. cm. with intermediate polishing. The Ti replicas were removed by electrolytic etching in a 10% aic. soln. of aqua regia at 0.5 amp./sq. cm. Electron micrographs at 7500X showed a fine internal structure within the austenite grains. The orientation and size of this block structure varied from one grain to another. Also, at grain boundaries there were regions of various widths with block structures different from that of the grain proper. Occasional grains contained regions in which the block structure was of different orientation. At the boundary of a carbide particle the block structure was also different. A. G. Guy

KVASHNINA, Ye. I.

USSR

Influence of carbide-forming elements on temper brittleness of steels. V. I. Prosvirina and E. I. Kvashnina. *Vestnik Mashinostroyeniya* 35, No. 2, 1987 (1988), 11-12. In order to find the mechanism through which Mo and W lower temper brittleness of steels, a series of steels were similarly heat-treated, tested for impact strength at -20 to -100° , and the sepd. carbides analyzed chemically and by x-rays. The Cr-Mo steels contg. C 0.35, Mn 1, and Cr 1.3% quenched from 860° in oil have 90% of their Mo in solid soln. When they are tempered at 650° and heated 100 hrs. at 500° , up to 0.44% Mo reduces brittleness; above 0.44% increases it. On reaching 1% Mo, the Mo₂C appears while the soln. of Mo in ferrite decreases. Different effects of Mo content are assocd. with the difference in its distribution between carbides and solid soln., the concn. in the latter being the real cause. In a steel with 0.44% Mo, a redistribution of alloying elements in carbides takes place at 500° , but the total vol. of carbides remains const., while in the same steels, but in the absence of Mo, addnl. carbides ppt. without any changes in compn. Atoms of Mo in solid soln. and having a strong affinity for C interfere with free diffusion of the latter and formation of stable compds. with Fe, Mn, etc., which interferes with the development of cementite crystals. When there is less Mo than required for combining with C, cementite ppts.; when more, Mo₂C leaves solid soln., in both cases causing embrittlement. In Cr-Mn steels contg. C 0.32-0.38, Mn 1, Si 0.3, Cr 1.01-1.00, and W 0.6-2.4%, quenched from 860° in oil and tempered for 2

hrs. at 650°, the impact strength decreased with the time of cooling after tempering, W reducing this effect; 1.5% W makes it independent of cooling rate when tested at 20°, greater and smaller concns. both influencing it. Abs. impact figures were highest under any conditions for 0.9-0.8% W steels. After heating tempered and water-cooled samples at 500° for 10-500 hrs. and testing at 20°, all alloys, with the exception of the one contg. 1.55% W, showed a decrease to a min. and then an increase with a longer heating time. The impact strength of the 1.5% W steel remained const. Impact testing at +20 to -100° demonstrated a shifting of the transition point upwards with a longer heating time, but W up to 1.5% retarded it and then speeded the shifting. About 90% W in samples tempered at 650° is in solid soln. when the element is under 1.85%, but with a greater concn. of W its percentage in carbides increases, but no changes in the structure of the carbide phase occurs on passing from the ductile to the brittle state. In Cr-Ni steels with C 0.3, Si 0.3, Mn 0.6, Cr 0.80-1.40, Ni 1.08-3.20%, addn. of 0.8-1.55% W increases toughness of thermally embrittled steel in the +20 to -80° range proportionally to its content. Replacing Mo with W in Cr-Ni-Mo steel and aging showed at -60° a drop in impact strength directly proportional to W content. Neither Ti, V, nor Nb have any effect on embrittlement.

J. D. Gal

M. J. Gal

Kvashnina, Ye. I.

USSR / Phase Conversions in Solids.

E-5

Abs Jour : Ref Zhur - Fizika, No 4, 1957, No 9307

Author : Prosvirin, V.I., Kvashnina, Ye. I.

Title : Concerning the Nature of the Temper Brittleness of Pearlitic Steels.

Orig Pub : Metallovedeniye i obrabotka metallov, 1956, No 2, 24-49

Abstract : It is shown for structural steels that the kinetics of the development of brittleness is in principle the same for all brands of steel. Using the methods of carbide and X-ray structural analysis it is established that the secondary phase in the viscous and brittle states is the carbide of the cementite type with dissolved carbide-forming elements. The crystallographic structure of the secondary phase does not change when the steel changes from the viscous state into brittle, but the amount of this phase increases. An increase the amount of carbide phase as the result of heat

Card : 1/2

USSR / Phase Conversions in Solids.

E-5

Abs Jour : Ref Zhur - Fizika, No 4, 1957, No 9307

Abstract : ting is observed in the zone of the development of the brittleness also after a prolonged high-temperature tempering; this is not observed when the steel is alloyed with 0.5% Mo. This action of Mo is observed when the contents of the latter is optimum for each brand of steel. It is established that in the case of optimum content, all the molybdenum is in solution and retards strongly the carbide formation. It is proposed that this also prevents the development of brittleness. The mechanism of the development of brittleness is connected with the fact that as the limit of solubility of carbon in α -iron is approached in tempering, the separation of the last portions of carbon is strongly retarded. Under these conditions new portions of carbide are formed in the boundary zones of the crystals in plate-like forms, which causes a reduction in the impact viscosity.

Card : 2/2

PROSVIRIN, V.I., doktor tekhnicheskikh nauk, professor; KVASHNINA, Ye.I.,
kandidat tekhnicheskikh nauk.

The nature of temper brittleness in perlite steel. Metalloved. i
obr. met. no.2:34-49 F '56. (MIRA 9:7)

1. Tsentral'nyy nauchno-issledovatel'skiy institut tyazhelego
mashinostroyeniya.
(Perlite) (Steel--Brittleness)

AUTHOR: Kvashnina, Ye. I., Candidate of Technical Sciences. 616
(TsNIITMASH).

TITLE: Electron-microscopic investigation of the structure of the steel 1X18H9T after various conditions of heat treatment. (Elektronno-mikroskopicheskoye issledovaniye struktury stali 1X18H9T Posle razlichnykh rezhimov termicheskoy obrabotki).

PERIODICAL: "Metallovedenie i Obrabotka Metallov" (Metallurgy and Metal Treatment), 1957, No.5, pp.35-38 (U.S.S.R.)

ABSTRACT: Comparison of the measured values of the impact strength and of the micro-structure in the case of differing hardening temperatures does not provide an explanation of the sharp increase of the impact strength as a result of an increase in the hardening temperature above 1050°C. For clarifying the structural changes taking place in a steel containing 0.11% C; 1.20% Mn; 0.42% Si; 17.9% Cr; 10.06% Ni; 0.50% Ti; 0.021% S; 0.02% P, investigations were carried out by means of an electron-microscope. After etching the polished specimens a titanium film was deposited by evaporation in vacuum and this film was removed by electrolytic etching in a 10% alcoholic solution of aqua regia. Fig.1 shows two photos of the micro-structure (magnification 7500 times) obtained for heating temperatures of 1150 and 1050°C respectively; Fig.3

Card 1/2

616

Electron-microscopic investigation of the structure of the steel 1X18H9T after various conditions of heat treatment. (Cont.)

shows three photos of the micro-structure for the steel after hardening at 1200°C and ageing for 1000 hours at 575°C, for ten hours at 800°C and for 500 hours at 800°C respectively. The investigations enabled to detect new features in the structure of the studied steel and to indicate the structural changes which produce a change in the mechanical properties resulting from the heat treatment. 1 Table, 2 Figures (photographs).

Card 2/2

KVASHNINA, Ye.I., kandidat tekhnicheskikh nauk.

"Microscopic investigation of metals" by E.E. Levin. Reviewed by
E.I. Kvashnina. Metalloved.i obr.met. no.7:60-61 J1 '57. (MLRA 10:8)

(Metallography) (Levin, E.E.)

PHASE I BOOK EXPLOITATION SOV/5511
Nauchno-tekhnicheskoye obshchestvo mashinostroyitel'noy promyshlennosti.
Kiyevskoye oblastnoye pravleniye.

Metallovedeniye i termicheskaya obrabotka (Physical Metallurgy and Heat
Treatment of Metals) Moscow, Mashgiz, 1961. 330 p. Errata slip
inserted. 5,000 copies printed.

Sponsoring Agency: Gosudarstvennyy nauchno-tekhnicheskyy komitet
Soveta Ministrov UkrSSR. Nauchno-tekhnicheskoye obshchestvo
mashinostroyitel'noy promyshlennosti. Kiyevskoye oblastnoye
pravleniye.

Editorial Board: M. P. Braun, Doctor of Technical Sciences, I. Ya.
Dekhtyar, Doctor of Technical Sciences, D. A. Dravyn, Doctor of
Technical Sciences, I. S. Kamnichnyy, Engineer, Ye. A. Karkov-
skiy, Candidate of Technical Sciences, V. G. Peryvskoy, Doctor
of Technical Sciences, and A. V. Chernovol, Candidate of Tech-
nical Sciences; Ed.: M. S. Soroka; Tech. Ed.: M. S.
Gornatskiy; Chief Ed., Mashgiz (Southern Dept.): V. K.
Sevdyuk, Engineer.

Card 1/40

PURPOSE: This collection of articles is intended for scientific
workers and technical personnel of research institutes, plants,
and schools of higher technical education.

COVERAGE: The collection contains papers presented at a convention
held in Kiyev on problems of physical metallurgy and methods of
the heat treatment of metals applied in the machine industry.
Phase transformation of austenite into martensite under high
pressure, results of investigations conducted to ascertain the effect of
heat treatment on the quality of metal are analyzed. The pos-
sibility of obtaining metals with given mechanical properties
is discussed, as are problems with steel brittleness. The col-
lection includes papers dealing with kinetics of transformation,
heat treatment, and properties of cast iron. No personalities
are mentioned. Articles are accompanied by references, mostly
Soviet.

TABLE OF CONTENTS:

Streghulin, A. I., Engineer, and L. A. Mel'nikov (Sverdlovsk). Transformation of Austenite into Martensite Under High Pressure	12
Brusilovskiy, B. A., Engineer, and P. I. Ivanov (Kramatorsk). X-Ray Investigation of the Decomposition Kinetics of Martensite in Tempering at Low Temperature	19
Kocherzhinskiy, Yu. A., Candidate of Technical Sciences (Kiyev). Conditions of Formation of Metastable Austenite in Iron-Carbon Alloys	22
Mirovskiy, E. I., Engineer (Kiyev). The Nature of the Phase Transformation of Carbon Steels	34

Card 3/40

Physical Metallurgy (Cont.)	SOV/5511
Blanter, M. Ye., Doctor of Technical Sciences, Professor, N. A. Kulakov, Engineer, and I. M. Sergeychev (Moscow). Quench-hardening of Massive Steel Parts in Water-Air Mixtures	167
Braun, M. P., and B. B. Vinokur (Kiyev). Character of Rupture of Chromium-Nickel-Niobium Steel	182
Asanov, A. D., Candidate of Technical Sciences (Moscow). Effect of High-Temperature Heating on the Strength Proper- ties of Steel	189
Kondrakhov, A. I., Engineer, K. P. Gurzhmyenko, and N. M. Koleznik (Kramatorsk). Accelerated Heating and Cooling Regimes in the Heat Treatment of Large Forgings	196
Kostyrko, O. S., Engineer, Ye. P. Dobrynskiy (Magnitogorsk), and N. P. Braun. Development of a Rational Heat-Treatment Regime for Large Forgings	203
Physical Metallurgy (Cont.)	SOV/5511
Vinokur, B. B. (Kiyev). Heat Resistance of Various Alloyed Steels	215
Vanin, V. S., Engineer, and V. K. Titov (Nikolayev). Concentration of Steel in Liquid Organic Media	225
Bulin, K. P., Corresponding Member of the Academy of Sciences, Ukrainian SSR (Dnepropetrovsk), and A. V. Chernovol, Candidate of Technical Sciences (Kiyev). On the Graphite Growth in Cast Iron	229
Zubarev, V. P., Doctor of Technical Sciences, Professor, and P. K. Tkachenko, Engineer (Zhdanov). On the Mechanism of the Silicon Influence on Graphitizing	234
Popova, N. N., Engineer (Kharkov). Investigation of the Growth of Gray Cast Iron	242
Yatsenko, A. I., Engineer (Dnepropetrovsk). Structural Changes in Austenitizing Ferritic Magnesium Iron	249
Physical Metallurgy (Cont.)	SOV/5511
Zubarev, V. P., Doctor of Technical Sciences, Professor, P. K. Tkachenko, and L. N. Kudryavtsev (Zhdanov). For- mation of Graphitization Centers and Special Features of Their Distribution in the Annealing of Quenched White Cast Iron	258
Titov, V. K., Engineer, and V. S. Vanin (Nikolayev). The Quenching of White Cast Iron and Its Effect on the Graphitization of Segregated Cementite	266
Dubrov, V. V., Engineer (Kiyev). Investigating the Isothermal Decomposition of Cementite in Farganese Cast Iron	270
Babro, Yu. G., Candidate of Technical Sciences, Docent (Kharkov). Effect of Certain Elements on the Properties of Manganeze Cast Irons	281
Kvashina, Ye. I., Engineer (Moscow). Optimum Heating and Cooling Rates in Annealing of High-Strength Spheroidal- Graphite Iron Castings Card 9/10	292
Physical Metallurgy (Cont.)	SOV/5511
Konenova, T. A., Engineer (Moscow). Investigating the Properties of Quenched Manganeze Cast Iron	302
Dykhovskiy, A. I., Engineer (Kiyev). Effect of Heat Treatment on the Transformation of White Tin Into Gray	317

1ST AND 2ND GROUPS		PROCESSING AND PROPERTY INDEX	
AM		KAVANISHA (Mme E. S.). Bozani Tabaka u Chumukom pahua's ... [Tobacco diseases in the Soteli area of the Black Sea district according to observations in 1929.] - Bull. North Caucasian Plant Prot. Stat., Rostov-on-Don, 1930, 6-7, pp. 217-260, 7 figs. 1 graph, 1930. (German summary. Received June, 1931.)	
In this paper, brief preliminary accounts are given of the chief diseases of tobacco (<i>Nicotiana glauca</i>) recorded in 1929 in the Soteli area of North Caucasus. The most important was that locally known as "ryaboukha" [R.A.M. s. p. 412 and next abstract]. in which the following six forms of leaf spotting may be macro- scopically distinguished, the first three being definitely of bacterial origin, while the cause of the others is as yet unknown: (1) A form closely resembling the American wildfire [<i>Bacterium tabaci</i>]. (2) Rounded brown spots with concentric zones of necrotic tissue, which first appear on the under side of the leaves as diffuse, silvery-whitish spots bearing minute black necrotic dots. (3) Small spots, not over 1.5 mm. in diameter, chiefly found on the seedlings, first of an intense green colour, later growing larger and turning brown, rounded, frequently confluent convex on the upper side or with a narrow raised margin and usually crowded at the apical portion of the leaf. (4) White or creamy rounded or angular, usually rounded spots, from 0.5 to 1.5 mm. in diameter with a narrow, dark, raised margin dispersed over the whole leaf.			
ASS-SLA METALLURGICAL LITERATURE CLASSIFICATION		13001 804179	
13001 804179		13001 804179	

on erect, usually propped on one longitudinal half, and often perforated owing to the breaking away of the infected tissue. This form appeared to be most frequent on plants exposed to direct sunlight. (3) Rounded or irregular, frequently lobate, white to brown spots about 1.5 to 2 mm. in diameter, with a narrow, dark raised margin, rather rare. (4) Irregularly angular, brown usually colored spots 0.5 to 1 mm. in diameter with a raised

white fleck and a dark, raised margin; this type was only observed in small quantity on a local variety. Form (4) was occasionally found associated with *Ascochyta nicotianae* [ibid., ix, p. 227], and the spots of forms (5) and (6) frequently bore later in the season pycnidia of an undetermined species of *Phyllosticta*, differing from *P. tabaci* [loc. cit.] in the size of its spores. The relationship of this organism to the disease is being investigated. No great variations were observed in the susceptibility of the tobacco varieties cultivated in the region to 'ryaboukha', but healthy individual plants were often found growing among heavily infected ones, a fact which would indicate the possibility of developing resistant strains by selection.

Among the other diseases described the following may be mentioned: A severe seedling blight, associated with leaf-spotting, which developed in the seed-beds under glass of an important nursery during a prolonged spell of foggy and drizzling weather; although the cause of this blight was not established, it is believed to have been of bacterial origin. Some varieties suffered heavily

AM

from a bacterial disease locally known under the name 'dikyi
ogon' [wildfire], characterized by the appearance on the under side
of the leaves of indistinct, whitish spots, on which later develop
minute, oily, green flecks which increase in size, run together, and
finally form continuous spots between the veins, usually extending
on both sides of the midrib, but not reaching the margin of the
leaf. Later the affected tissue dries up and falls out. In one
locality tobacco seedlings were severely attacked by *Botrytis*
cineris, which caused a stem rot near the collar. This fungus was
also found on the flowers and seed pods of tobacco plants, which
were rotted by it [cf. *ibid.*, vii, p. 547]. Tobacco mosaic was
observed in one plantation; the symptoms of the disease were
greatly intensified in September, after a heavy rainfall.

ASD-11A METALLURGICAL LITERATURE CLASSIFICATION

AM

КВАНШИННА (Минс Е. С.). Бактериальный гоммоз Хлопчатника на Таманском полуострове по данным наблюдений в 1931 г.
 [Bacterial gummosis of Cotton in the Taman peninsula, according to observations in 1931].—*Dall. N. Caucasian Inst. for Plant Protection*. Rostoff-on-Don, i (viii), 2, pp. 52-68, 2 pl., 2 graphs, 1933. [English summary.]

This is a detailed account of a generalized bacteriosis of the cotton plant which was very prevalent in 1931 in the newly established cotton fields in the Taman peninsula [Black Sea littoral of Northern Caucasus]. The disease [which has been attributed to *Bacterium malvacearum* and some other forms: R.A.M. xi, pp. 41, 316] affected the cotyledons, stems, petioles, leaves, and bolls, producing symptoms which are described and are stated to resemble closely those associated with angular leaf spot and black arm of cotton, including a severe boll and lint blight. The epidemic outbreak of the disease in 1931 is chiefly ascribed to the exceptionally wet weather which prevailed from May to September, the total rainfall for that period being 341 mm. as compared with the local normal average of 151.5 mm. From September onwards, as the weather became more settled, the incidence and severity of new infections decreased, with the result that the later pickings of the crop were considerably healthier than the earlier.

ASS. SLA METALLURGICAL LITERATURE CLASSIFICATION

Field observations in several localities indicated the existence of varietal differences in the relative resistance to the disease of 26 varieties of American Upland cottons (*Gossypium hirsutum*) which were experimentally grown, although none of them was completely immune. In this group the varieties 1306, 2013, and 182 were the least severely attacked by the stem and boll forms of the disease, which are stated to be the most destructive under the local conditions. Varieties of *G. herbaceum*, as a class, showed considerably greater resistance, and some of them gave indications of complete immunity.

There was further evidence that sowing cotton on autumn-fallowed soil tended to reduce the incidence of early infections.

Tests with various manures showed that applications of a fertilizer containing phosphorus and potassium reduced the incidence of the disease from 83.5 per cent. in the control to 31.3 per cent., while applications of a nitrogenous fertilizer reduced the percentage of attack to 25.6. The use of relatively resistant varieties, e.g., Upland 1306, may also tend to minimize the losses.

- - - KVASHNINA, E. S.

KVASHNINA, E. S. "Tobacco Diseases in the Sochi Region of the Black Sea District According to Observations in 1929," Izvestiia Severo-Kavkazskoi Kraevoi Stantsii Zashchity Rastenii, no. 6-7, 1930, pp. 247-260. 423.92 Se8

SO: SIRA SI-90-53, 15 Dec. 1953

KVASHNINA, E. S.

KVASHNINA, E. S. "Gummosis of Cotton on Taman Peninsula, in 1931,"
Biulleten' VII Vsesoiuznogo S'ezda po Zashchite Rastenii
v Leningrad 15-23 Noiabria 1932 Goda, no. 8, 1932, pp. 25-26
423.92 V96

SO: SIRA SI-90-53, 15 Dec. 1953

KVASHNINA, E. S.

KVASHNINA, E. S. "Bacterial Gummosis of Cotton in the Taman Peninsula,
According to Observations in 1931," Trudy Severo-
Kavkazakogo Instituta Zashchity Rastenii, vol. 1
(8), no. 2, 1933, pp. 52-68. 423.92 Se8

SO: SIRA CI-90-53, 15 Dec. 1953

1ST AND 2ND ORDERS										3RD AND 4TH ORDERS									
PROCESSES AND PROPERTIES INDEX																			
<p><i>Handwritten: 15</i></p> <p>Fungicidal properties of hydrogen sulfide. R. S. Kyashina. <i>Trudy Zashchity Rastenii (Bull. Plant Protection)</i> Ser. III, 67-64(1935); <i>Rev. Applied Mycol.</i> 15, 670; cf. preceding abstr. Higher temps. are more important in the use of H_2S as a fungicide than either increase in concn. or length of exposure of seed. Field tests showed generally that as good or better stands were obtained when H_2S was used as when formalin was used and good control of the various parasitic and saprophytic fungi contaminating the wheat, barley, oats, maize and cabbage seed was obtained. Oden R. Sheppard.</p>																			
<p>ASB-514 METALLURGICAL LITERATURE CLASSIFICATION</p>																			
<p>1ST AND 2ND ORDERS</p>										<p>3RD AND 4TH ORDERS</p>									

1ST AND 2ND ORDER										3RD AND 4TH ORDER									
PROCESSES AND PROPERTIES INDEX																			
<p>CP</p>										<p>15</p>									
<p>The fungicidal properties of sulfides (hydrogen sulfide, sulfurous slag) and elaboration of methods for their use in seed disinfection. E. S. Kvashina and Z. S. Bismakova. <i>Sov. Sci. Res. Wk. Inst. Pl. Prot. Leningrad</i> 1933, 416-19(1936); <i>Rev. Applied Mycol.</i> 16, 21-7. Field exper. confirm the efficacy of H_2S in the control of wheat bunt (<i>Tilletia caries</i> and <i>T. foetida</i>), barley-covered smut (<i>Ustilago hordei</i>), loose smut of millet (<i>Panicum miliaceum</i>), wheat, barley and oats (<i>U. panicumilaceae</i>, <i>U. tritici</i>, <i>U. secalis</i> and <i>U. avenae</i>). Exposure of dry seed grain to atmos. conc. 400 g. (liquid) H_2S per cu. m. for 72 hrs. did not adversely affect either the germinability of the seed or the yield of the ensuing crops. H_2S reduces the germinability of damp seed, but such seed may be mixed satisfactorily with granulated blast-furnace slag at the rate of 4 to 8 kg. per cu.-m. of the enclosed space with good results. Oden H. Sheppard</p>																			
<p>ASB-51A METALLURGICAL LITERATURE CLASSIFICATION</p>																			
<p>FROM STUDYING</p>										<p>FROM INDEXING</p>									
<p>1ST AND 2ND ORDER</p>										<p>3RD AND 4TH ORDER</p>									

KVASININA, E. S.

KVASININA, E. S., and YEMISHEVA, Z. S. "Studies on the Fungicidal Properties of Sulfides and Elaboration of Methods for Their Use in Seed Disinfection,"
Itogi Nauchno-Issledovatel' skikh Rabot Vsesoiuznogo Instituta Zashchity Rastenii, za 1935
no. 9, 1938, pp. 36-86. 464.9 R73

So: SIRA SI 90-53, 15 December 1953

KVAS-NINA, E. S.

KVAS-NINA, E. S. "Fusariosis of Wheat in the Azov-Black Sea Area," Izvestiia Rostovskoi Stantsii Zashchity Rastenii, no. 9, 1938, pp. 36-86. 464.9 R73

SO: SIRA SI 90-53 15 December 1953

KVASHNINA, E. S.

KVASHNINA, E. S. "Diseases of Seed of Timber Stock and Methods of Disinfection,"
Sotsialisticheskoe Zernovoe Khoziaistvo, no. 5, 1939, pp. 134-139. 59.8 So72

SO: SIRA SI 90-53 15 December 1953

1ST AND 2ND ORDERS																										PROCESSES AND PROPERTIES INDEX																										3RD AND 4TH ORDERS																									
CA																										<p>New toxico-biological properties of <i>Fusarium sporotrichoides</i>. A. Kh. Sarkisov and R. S. Kvashnina. <i>Doklady Akad. Nauk S.S.S.R.</i> 63, 77-9(1948).—This species is shown to be extremely toxic to lab. animals, horses, and hogs. The symptoms are parallel to those exhibited by human subjects after consumption of winter wheat grains. Cultures grown at 1.5-4° are more toxic than those grown at higher temps.; this organism is killed by exposures to 100° for 10 min., but not by chilling to -20° even for 4 months. The toxic principle is sol. in org. solvents and is stable at 120°; it is similar to that of winter grain, in that Et₂O-extd. fatty fraction has similar action to similarly extd. grain fraction. Hence, the toxic properties of winter grain may be due to the growth of this fungus.</p> <p>G. M. Kosolapoff</p>																										11c																									
ASAC-5LA METALLOGICAL LITERATURE CLASSIFICATION																										FROM: 574-2314																										11000 804100																									
11000 804100																										11000 804100																										11000 804100																									

KVASHNINA, Ye. S.

USSR/Biology
Fungus
Toxicology

Nov 48

"New Biologically Toxic Characteristics of the Fungus Fusarium Sporotrichioides Sherb.," A. Kh. Sarkisov, Ye. S. Kvashnina, All-Union Sci Res Lab for Study of Toxic Fungi, Min of Agr USSR, Moscow, 2 $\frac{1}{2}$ pp

"Dok Ak Nauk SSSR" Vol LXIII, No 1

Series of studies show that grain crops remaining under snow through the winter become poisonous due to presence of Fusaria sporotrichioides. Cultural and morphological studies of toxic varieties proved they do not differ from those described in literature, Submitted by Acad B. L. Isachenko 4 Sep 48.

61/49T12

KVASHNINA, E.S.

The Administration of Scientific Research Establishments, Main Administration of Agricultural Propaganda, USSR Ministry of Agriculture, held the first All-Union Scientific Practical Conference, ^{on chronic bovine hematuria} at the All-Union Scientific Research Laboratory for the Study of Toxic Fungi. The conference date was 26-28 September 1950. A series of reports were heard at the conference on chronic bovine hematuria. Candidate of Agricultural Sciences E. S. Kvashnina (All-Union Scientific Research Laboratory for the Study of Toxic Fungi) reported on "The Problem of the Role of Fungi in the Etiology of bovine hematuria". * ~~Page 5~~
 SO: Veterinariya; Vol. 27; No. 12; 53-55; December 1950 uncl de g
 Trans. # 242 by L. Lulich

* Work on chronic bovine hematuria by the All-Union Scientific Research Laboratory for the Study of Toxic Fungi by KVASHNINA in collaboration with O. A. Gavrilova and P. A. Gerasimova have shown that various toxic fungi do not contribute directly to the etiology of this disease.

KVASHNINA, E.S.
USSR / Microbiology. Antibiosis and Symbiosis. Antibiotics F-2
Abs Jour : Ref Zhur - Biol., No 1, 1958, No 615
Author : Kvashnina, E.S.
Inst : Not Given
Title : On Interrelationships Among Fusarium Species Infecting Feeds
Orig Pub : Ryul. nauchrotekhn. inform. Vses. n.-i. in-t vet. sanitarii
i ektoparazitol., 1957, No 2, 53-54
Abstract : No abstract

Card : 1/1

KVASHNINA, Ye.S.

Determination of the content of antibiotic in fodder oxy-
tetracycline by the fluorescence method. Antibiotiki 8
no.1:76-78 Ja'63. (MIRA 16:6)

1. Laboratoriya antibiotikov (zav. - prof. A.Kh.Sarkisov)
Vsesoyuznogo instituta eksperimental'noy veterinarii.
(OXYTETRACYCLINE) (FLUORESCENCE)
(FEEDS--ANALYSIS)

KVASHNINA, Ye. S.

"Method of selection of high-producing variants of act. Rimosis for the surface fermentation of oxytetracycline."

report submitted for Antibiotics Cong, Prague, 15-19 Jun 64.

Antibiotical Lab, All-Soviet Inst of Experimental Veterinary Medicine, Moscow.

KURASOVA, V.V.; KVASHNINA, Ye.S.; KADYROV, N.T.; IBRAGIMOV, R.P.;
MOREV, V.I.; ROGOZHNIKIN, A.I.; SIROTENKO, M.

Information. Veterinariia 38 no.11:92-96 N '61 (MIRA 18:1)

AUTHORS: Kvashonkin, I.A., and Lyubimov, K.V. (Leningrad) SOV-47-58-6-23/28

TITLE: Markings in Radio-Engineering Diagrams (Oboznacheniya v radiotekhnicheskikh skhemakh)

PERIODICAL: Fizika v shkole, 1958, Nr 6, pp 77 - 78 (USSR)

ABSTRACT: A table of 54 conventional designations for parts of radio-engineering diagrams which are encountered when in a school course in physics and electro-engineering is given.

1. Physics---Study and teaching

Card 1/1

137-58-4-8332

Translation from: Referativnyy zhurnal, Metallurgiya, 1958, Nr 4, p 289 (USSR)

AUTHOR: Kvashuk, N. F.

TITLE: The Technical and Economic Results of the Employment of Low-alloy Steel in the Building of Merchant Ships (Tekhnicheskiy i ekonomicheskiy effekt primeneniya nizkolegirovannoy stali dlya postroyki sudov grazhdanskogo flota)

PERIODICAL: Tr. nauchno-tekhn. o-va sudostroito, prom-sti, 1956, Vol 7, Nr 1, pp 51-65

ABSTRACT: The author presents the results of analytical calculations of the technical and economic effect of the use of SKhLl steel for the hulls of dry-cargo carriers and tankers as compared to hulls of equal strength made of St. 4s steel. The author comes to the conclusion that present low-alloy steels (SKhLl) are not suitable for merchant shipbuilding. The use of SKhLl steel is unavoidable at present because of the shortage of ordinary carbon steels that are readily weldable in thick plate form. Low alloy steels can give good technical and economic results if their corrosion resistance can be made to be at least 50 to 100% greater than that of St. 4s steel at a σ_s of the same order as SKhLl steel,

Card 1/2

137-58-4-8332

The Technical and Economic (cont.)

all other mechanical properties being adequate. See RzhMet, 1958, Nr 1, abstract 1772.

1. Ship hulls--Materials--Effectiveness 2. Ship hulls--Materials
--Economic aspects 3. Steel--Applications

A.M.

Card 2/2

SHEVANDIN, Ye.M., kand. tekhn. nauk; KOZLYAKOV, V.V., kand. tekhn. nauk;
MAKSIMADZHI, A.I., inzh.; BYKOV, V.A., kand. tekhn. nauk;
YEVSTIFEYEV, V.A., kand. tekhn. nauk; BELKIN, V.P., doktor
tekhn. nauk; REZNITSKIY, L.Ya., kand. tekhn. nauk; PUTOV, N.Ye.,
prof.; SHIMANSKIY, Yu.A., akademik; GUREYEV, V.A., inzh.;
VAKHARLOVSKIY, G.A., inzh.; KERICHEV, V.M.; KVASHUK, N.F.,
inzh.; NOGID, L.M., prof.; REVZYUK, G.A., inzh.; ARKHANGORODSKIY,
A.G., kand. tekhn. nauk; YEFREMOV, inzh.; OSMOLOVSKIY, A.K.,
kand. tekhn. nauk.

General discussion. Trudy NTO sud. prom. 7 no.1:112-152 '56.

(MIRA 10:12)

1. TSentral'nyy nauchno-issledovatel'skiy institut im. A.N. Krylova
(for Shevandin). 2. Leningradskiy korablestroitel'nyy institut
(for Kozlyakov, Bykov, Putov, Nogid). 3. TSNIISTEP (for Maksimadzi).
4. TSentral'noye konstruktorskoye byuro Ministerstva sudostroitel'-
noy promyshlennosti, g. Gor'kiy (Yevstifeyev, Kvashuk, Revzyuk).
5. TSentral'noye-proyektno-konstruktorskoye byuro Ministerstva
morskogo flota (for Reznitskiy). 6. Ministerstvo sudostroitel'noy
promyshlennosti (for Gureyev). 7. Gosudarstvennyy soyuznyy projektnyy
institut (for Vakharlovskiy). 8. Zavod "Krasnoye Sormovo" (for
Kerichev). 9. NKI (for Arkhangorodskiy). 10. Ministerstvo rechnogo
flota (for Yefremov). 11. TSentral'nyy nauchno-issledovatel'skiy
institut morskogo flota (for Osmolovskiy).

(Shipbuilding)

KVASHUK, N.F., inzh.

Assembly joint of transverse bulkheads with bottoms in tank vessels.
Sudostroenie 25 no.8:7-9 Ag '59. (MIRA 13:2)
(Tank vessels) (Bulkheads (Naval architecture))

L 45149-66 EWT(m)/EWP(t)/ETI IJP(c) JD/WB
ACC NR: AP6014738 (N) SOURCE CODE: UR/0229/65/000/011/0015/0020

AUTHOR: Kvashuk, N. F.; Kontorovich, B. M.

ORG: none

TITLE: Designing and building ship hulls for the Soviet maritime fleet

SOURCE: Sudostroyeniye, no. 11, 1965, 15-20

TOPIC TAGS: shipbuilding engineering, cargo ship, electrosag welding, alloy composition, corrosion protection

ABSTRACT: The authors review the problems of design, building, and electric welding of hulls of maritime transport ships and analyze means to deal with the designing of metal hulls of vessels and the use of high-strength steel during the past years. The use of light alloys and basic changes in the design of metal hulls of transport ships are discussed. Some information is given on shipbuilding technology and protection of the body of a vessel against corrosion. Orig. art. has: 4 figures. [NT]

SUB CODE: 13/ SUBM DATE: none/

Card 1/1 *aym*

KVASHUK, N.F.; KONTOROVICH, B.M.

Designing and building the hulls of ships of the Soviet
transport fleet. Sudostroenie no.11:15-20 N '65
(MIRA 19:1)

BROKSH, M.M.; GVOZDEV, B.P.; KVASHUK, V.S.; KOSHELEV, V.A.

Using cermet filters to remove solid impurities from natural
gas. Trudy VNIIGAZ no.21/29:205-217 '64. (MIRA 17:9)

Kvasil, B.

KVASIL, B.

621.372.413 : 621.317.355.3 : 621.317.41
 18841. Measurement of complex permittivity and permeability in cavity resonators. B. KVASIL. Slaboproudý Obzor, 16, No. 5, 227-37 (1955). In Czech.

Analysis of a cavity resonator completely filled with a dielectric material (liquid or gas) shows that this method is only suitable for the measurement of low-loss materials with small relative permittivity. In general, a measured sample occupies only a small portion of the total resonator's volume. The case is analysed in detail; general expressions relating the complex permittivity and permeability of the sample to the geometry, volume, resonant frequency and quality factor of the resonant cavity are derived. If the sample is placed in zero magnetic field, the expressions become simplified and the permittivity can easily be evaluated; the measurement of permeability is carried out by placing the sample in zero electric field. Approximate expressions for the parameters of a small sample, placed in a rectangular cavity are evaluated for TE_{101} and TE_{102} waves. A more accurate analysis shows that the approximate formulae are valid, provided that the volume of the sample is sufficiently small. The case of a cylindrical cavity resonator with TM_{010} wave is also considered.

N. S. Sidorowicz

M

KVASIL, B.

Use of millimeter waves in radiolocation and telecommunication. p! 260.

SDELOVACI TECHNIKA. Vol. 4, no. 9, Sept. 1956

Praha, Czechoslovakia

SOURCE: East European List (EEAL) Library of
Congress, Vol. 6, No. 1, January 1957

KVASIL, BOHUMIL

Category : CZECHOSLOVAKIA/Radiophysics - Radiation of Radio Waves. Antennas I-5

Abs Jour : Ref Zhur - Fizika, No 2, 1957, No 4496

Author : Kvasil, Bohumil

Title : Rapid Deflection of an Electromagnetic Beam Radiated by a Metallic Lens

Orig Pub : Slaboproudý obzor, 1956, 17, No 5, 243-247

Abstract : A detailed analysis is given of the distribution of the phase of the electric field intensity on the output surface of a metallic lens in the case of a radiator, shifted in a direction perpendicular to the axis of the lens. Based on the equations derived for the phase of the electric field intensity, such a method is proposed for zoning the input surface as to limit the cubic error and to insure as much as possible the linearity of the phase at the output surface when the primary radiator is shifted. Equations are derived for the input and output surfaces of the lens, taking into account the cubic error. The article is written from the point of view of using metallic lenses for rapid three-dimensional scanning in a vertical direction.

Card : 1/

KVASIL, B.

Rapid deflection of electromagnetic beams radiated by metal lenses.
(Conclusion) p. 309. (SLABOPROUDY OBZOR, Vol. 17, No. 6, June 1956,
Praha, Czechoslovakia)

SO: Monthly List of East European Accessions (EEAL) LC, Vol. 6, No. 12, Dec 1957. Uncl.

KVASIL, BOHUMIL

"Theoretické základy techniky centimetrových vln; celostatní vysokoskolská učebnice pro příslušné specializace na elektrotechnických fakultách. (Vyd. 1.) Praha, Statní nakl. technické literatury, 1957. (Theoretical principles of the technology of centimetric waves; a university textbook for specialized fields in faculties of electrical engineering. 1st ed. bibl., diagrs., graphs)"

303 p. (Praha, Czechoslovakia)

Monthly Index of East European Accessions (EEAI) LC, Vol. 7, no. 9
September 1958

KVASIL, B.

"Training of experts on nuclear physics in Czechoslovakia."

JADERNA ENERGIE. Praha, Czechoslovakia, Vol. 4, October 1958."

Monthly List of East European Accessions (EEAI), LC, Vol. 8, No. 8, September 1959.
Unclass.

KVASIL, B.

4E1C
4E3d

1989. RADIAL FUNCTIONS. B. Kvasil and V. Tysil.
Slaboproudý Obzor, Vol. 19, No. 1, PT-P8 (1988). In Czech.
The propagation of electromagnetic waves between two flat
parallel conducting rings (annuli) is considered. It is shown that the
voltage and current in the system (as a function of radial distance,
 r , from the origin) is given in terms of radial sines and cosines
which are expressed by means of Bessel and Neumann functions.
Expressions for the short- and open-circuit impedances of the sys-
tem are derived. The propagation between two non-parallel plates
is also analysed and it is again shown that the currents, voltages and
impedances are given in terms of radial functions. Application of
radial functions to the analysis of toroidal (klystron) resonators,
waveguide junctions and multi-cavity magnetrons is discussed and
illustrated by 3 numerical examples. R.S. Sidorowicz 1/1

aw R

KVASIL, B. ; HUSA, V.

Measurement of the conductivity of semiconductors in the microwave range. p. 667

SLABOPROULY OBZOR. (Ministerstvo presneho strojirenstve, Ministerstvo spoju a Vedecka technicka spolecnost pro elektrotechniku pri CSAV)
Praha, Czechoslovakia, Vol. 20, no. 11, Nov. 1959

Monthly List of East European Accessions (EEAI) LC, Vol. 9, no. 1,
Jan. 1960

Uncl.

4410
24.7700

89921
S/109/60/005/05/009/021
E140/E435

AUTHORS: Gusa, V. and Kvasil, B.

TITLE: Measurement of the Conductivity of Semiconductors in the Centimeter-waveband

PERIODICAL: Radiotekhnika i elektronika, 1960, Vol 5, Nr 5, pp 796-805 (USSR)

ABSTRACT: This report was read in October 1957 at a Meeting of the Section on Semiconductors of the First Congress of Czechoslovak Physicists.

A contactless method for measuring electrical conductivity of semiconductors, in particular Ge and Si, is described. The basic material may be of irregular shape and placed in a prismatic container. The measurement is carried out by determining the Q of a cavity resonator without sample and with sample. Because of surface phenomena the material must be granular rather than in powder form. There are 5 figures, 1 table and 4 references, 3 of which are English and 1 Czech.

SUBMITTED: April 13, 1959

Card 1/1

KVASIL, B.

"Radiophysical electronics" by N. A. Kapcov. Reviewed by B. Kvasil.
Jaderna energie 7 no.12: 410-411 D '61.

27326
Z/038/61/000/009/001/003
D257/D305

21.3/00

AUTHOR:

Kvasil, Bohumil

TITLE:

A contribution to calculating the geometric parameters of the accelerating tube of a high-frequency linear accelerator

PERIODICAL:

Jaderná energie, no. 9, 1961, 289 - 295

TEXT:

Calculating the geometric parameters of the accelerating tube of a high-frequency linear accelerator has to be made with extreme accuracy since even minute deviations of the phase velocity of the propagation of the electromagnetic waves from the correct value result in disruption of the synchronization between the particle and the electromagnetic field, and the particle is slowed down instead of being accelerated. The usual approach to solving this problem is to divide the accelerating space into two parts, i.e. the radial part between sectionalizing disks and the cylindrical waveguide part with a circular cross-section, as shown in Fig. 1. In the radial part the electromagnetic field is expressed using radial functions, and in the waveguide part by superposition of characteristic functions of the circular waveguide. On a radius $r=a$ the continuity of the tan-
Card 1/7

4

27396

Z/038/61/000/009/001/003

D257/D305

A contribution to calculating ...

gential components of the electric and magnetic fields intensity must hold true. If the functional series in both spaces can be expressed so that they converge uniformly, it will be possible to fulfill with a sufficient degree of accuracy the boundary condition on a radius $r=a$ and arrive at a fairly accurate formulation of a dispersion equation expressing the dependences between the tube dimensions, frequency and phase-propagation velocity. A new method of calculating this problem is proposed. It is based on the stationary difference of Poynting flows on the boundary between the radial and the cylindrical part. Its first approximation yields a result similar to that obtained by Chu and Hansen, namely

$$\frac{Z_1(ka, kb)}{Z_0(ka, kb)} = \frac{1}{1 + \frac{d}{D}} \cdot \frac{k}{\chi} \cdot \frac{J_1(\chi_0 a)}{J_0(\chi_0 a)} \quad (23)$$

where a is the inside diameter of the structure, b the inside diameter of the radial part, d the disk thickness, D the distance between disks, k the wave number of the free space, χ_0 the transvers propagation constant of the

Card 2/7

27396

Z/038/61/000/009/001,003

D257/D305

A contribution to calculating ...

mode 0, $Z_0(ka, kb) = J_0(ka) N_0(kb) - J_0(kb) N_0(ka)$, $Z_1(ka, kb) = J_0(ka) N_1(kb) - J_0(kb) N_1(ka)$, where J_0, J_1 are Bessel functions of the first order, and N_0, N_1 are Neumann functions. The second approximation is already much more accurate and much less complicated than that according to the Walkinshaw-Brillouin method, since it leads to a dispersion equation in the form of a transcendental equation:

$$\frac{Z_1(ka, kb)}{Z_0(ka, kb)} = \frac{1}{1 + \frac{d}{D}} \left[\frac{k}{\chi_0} \frac{J_1(\chi_0 a)}{J_0(\chi_0 a)} \left(\frac{\sin \gamma_0 \frac{D}{2}}{\gamma_0 \frac{D}{2}} \right)^2 + \frac{k}{\chi_1} \frac{J_1(\chi_1 a)}{J_0(\chi_1 a)} \left(\frac{\sin \gamma_1 \frac{D}{2}}{\gamma_1 \frac{D}{2}} \right)^2 \right] - \frac{2 \left(\frac{D}{D+d} \right)^2 \left[\frac{k}{\chi_0} \frac{J_1(\chi_0 a)}{J_0(\chi_0 a)} \frac{K_{00}}{D} \frac{K_{10}}{D} + \frac{k}{\chi_1} \frac{J_1(\chi_1 a)}{J_0(\chi_1 a)} \frac{K_{01}}{D} \frac{K_{11}}{D} \right]}{\frac{D}{D+d} 2 \left(\frac{k}{\chi_0} \frac{J_1(\chi_0 a)}{J_0(\chi_0 a)} \frac{K_{10}^2}{D} + \frac{k}{\chi_1} \frac{J_1(\chi_1 a)}{J_0(\chi_1 a)} \frac{K_{11}^2}{D} \right) - \frac{k}{\Gamma_1} \frac{Z_1(\Gamma_1 a, \Gamma_1 b)}{Z_0(\Gamma_1 a, \Gamma_1 b)}} \quad (30)$$

Card 3/7

A contribution to calculating ...

27396
Z/038/61/000/009/001/005
D257/D305

$$K_{00} = \frac{\sin \frac{\pi}{4} \frac{D}{D+d}}{\frac{\pi}{4} \frac{D}{D+d}} D;$$

$$K_{01} = \frac{\sin \frac{3\pi}{4} \frac{D}{D+d}}{\frac{3\pi}{4} \frac{D}{D+d}} D;$$

$$K_{10} = \frac{1}{4} \frac{\sin \left(4\pi \frac{D+d}{D} \right)}{\sin \left(\pi \frac{D+d}{D} \right)} \left[\frac{\sin \left(\gamma_0 - \frac{2\pi}{D} \right) \frac{D}{2}}{\gamma_0 - \frac{2\pi}{D}} + \frac{\sin \left(\gamma_0 + \frac{2\pi}{D} \right) \frac{D}{2}}{\gamma_0 + \frac{2\pi}{D}} \right];$$

Card 4/7

A contribution to calculating

27396
Z/038/61/000/009/001/003
D257/D305

$$K_{11} = \frac{1}{4} \frac{\sin\left(4\pi \frac{D+d}{D}\right)}{\sin\left(\pi \frac{D+d}{D}\right)} \left[\frac{\sin\left(\gamma_1 - \frac{2\pi}{D}\right) \frac{D}{2}}{\gamma_1 - \frac{2\pi}{D}} + \frac{\sin\left(\gamma_1 + \frac{2\pi}{D}\right) \frac{D}{2}}{\gamma_1 + \frac{2\pi}{D}} \right];$$

$$\gamma_0 = \frac{\pi}{2(D+d)}; \gamma_1 = \frac{3\pi}{2(D+d)};$$

$$\chi_0^2 = k^2 - \gamma_0^2; \chi_1^2 = k^2 - \gamma_1^2;$$

$$I_1^2 = k^2 - \left(\frac{2\pi}{D}\right)^2.$$

Card 5/7

A contribution to calculating ...

27396
Z/038/51/000/000/001/003
D257/D305

Where b_2 is the radius value as determined by the second approximation, b_1 is the radius value as determined by the first approximation.

Using Eq. (30) calculation of an accelerator disk was made for the case

$\frac{v_f}{c} = 0.7$; $a = 1.424$ cm; $d = 4$ mm; $D = 1.432$ cm. The dimension $b = 4.262$ cm

was obtained. It was established that this result, contrary to that obtained by the Hansen method, is in good agreement with the experiment within permissible tolerances. There are 2 figures and 4 references: 1 Soviet-bloc and 3 non-Soviet-bloc. The three references to English language publications read as follows: W. Walkinshaw, Pros. Phys. Soc, 61, 1947, 246; E.L. Chu, W.W. Hansen, J. Appl. Phys., 18, 1947, 966; W. Walkinshaw, J. Appl. Phys., 20, 1949, 634. 4

ASSOCIATION: Fakulta technické a jaderné fyziky ČVUT, Praha (Department of Technical and Nuclear Physics, ČVUT, Prague)

Card 6/7

24.6730

27872

Z/038/61/000/011/003/004
D291/D305

AUTHOR: Kvasil, Bohumil

TITLE: Approximate determination of the influences
exerted by characteristic-dimension tolerances
in the periodic structure of a linear r-f acce-
lerator and their compensation

PERIODICAL: Jaderná energie, no. 11, 1961, 378-383

TEXT: The article derives the relations for approximate cal-
culation of the influence exerted by radial dimensions of
the periodic structure of a linear electron accelerator on the
phase velocity of propagation, and discusses possibilities of
compensating for radial deviations by insertion of ferritic
or metal rods. The influence of geometrical tolerances can be
determined on the model of a cavity resonator, formed from a
4-disc section of the accelerator tube, and changes in the
characteristic frequency of this resonator can be used to derive

Card 1/5

27872
Z/038/61/000/011/003/004
D291/D305

Approximate determination...

changes in the phase-velocity of propagation. Both the phase velocity and the characteristic frequency are calculated with the aid of the approximation given by E. Chu and Hansen (Ref.1: J.Appl. Phys. 18 (1947), p. 996). The author demonstrates the identity of relations expressing the dependence between the dimensions of a cavity resonator and its characteristic frequency, and the dispersion equation for the periodic structure of an r-f accelerator (derived by Chu-Hansen), and thus proves the possibility of determining the dispersive properties of an accelerator tube by the dependence of the resonator's characteristic frequency on its geometrical dimensions. A change in the characteristic dimensions of a linear accelerator must, therefore, result in a change of characteristic frequency. The author then formulates the relations between the characteristic frequency of a cavity resonator and the phase-velocity of propagation, and formulates the characteristic

Card 2/5

27872

Z/038/61/000/011/003/004
D291/D305

Approximate determination...

frequency change in cases where the shape of the cavity resonator is disturbed, e.g. by changing one of its characteristic dimensions. He thus obtains a formula expressing the relative change of the characteristic wave number of a cavity resonator when its radius (b) is changed by a certain value (Δb) which, in turn, allows the relative change of the phase velocity to be calculated. Deviations from the correct dimensions of an accelerator tube can be corrected by compensation elements in the form of small dielectric or metal rods, inserted into the respective cavity resonator. The author lists then formulas for calculating compensation-rod volumes, necessary for the desired tuning effect. In cases where the actual radius is too small, the characteristic frequency of the cavity resonator will be higher (positive detuning), and viceversa (negative detuning). Ferritic elements can be used only to compensate for positive detuning, metallic elements are suitable to compensate for both positive and negative detuning, depending on whether they are

Card 3/5

Approximate determination...

27872
Z/038/61/000/011/003/004
D291/D305

inserted at the place of prevailing electric or magnetic energy respectively. A metallic compensation element can, therefore, be made in form of a screw and compensates at first for negative detuning (when inserted near the cavity wall where the influence of magnetic energy prevails), and subsequently for positive detuning (when driven towards the center of the cavity where the influence of electric energy prevails). According to the above-mentioned relations, the compensation elements correct detuned frequencies as well as phase velocities. In conclusion the author mentions that some mechanical influences on the phase velocity of electromagnetic-wave propagation in a periodic structure could be verified with the aid of an experimental cavity resonator built by the Electronics Department of the Faculty of Technical and Nuclear Physics. There are 10 figures and 3 references: 2 Soviet-bloc and 1 non-Soviet-bloc. The reference to the English-language publication reads as

✓

Card 4/5

Approximate determination...

27872
Z/038/61/000/011/003/004
D291/D305

follows: E.L. Chu - Hansen; J. Appl. Phys. 18 (1947), p 996.

ASSOCIATION: Fakulta technické a jaderné fyziky, ČVUT Praha
(Faculty of Technical and Nuclear Physics, ČVUT-
Czech Institute of Technology, Prague)

✓

Card 5/5

24 2300

39302
Z/026/62/007/003/003/003
D407/D301

AUTHOR: Kvasil, Bohumil, Professor, Doctor

TITLE: General solution of the electromagnetic field pattern in regions composed of sections with simple geometry

PERIODICAL: Aplikace matematiky, v. 7, no. 3, 1962, 227-235

TEXT: The article lists a method of calculating the distribution of an electromagnetic field in complex systems, based on the stationary state of the functional of the linear surface conduction current. This is an energetic method of electromagnetic-field calculation and a precision criterion is given for comparison with other methods. The calculation uses the model of a space composed of two sectional regions (V_1, V_2) surrounded by a metal coat (S) and separated by the contact areas (S_{12} and S_{21}). Sections V_1 and V_2 are of simple geometry, i.e. the wave or Helmholtz equation can be solved at the boundary condition that the tangential component of the electric-field intensity on the area S (including areas S_{12}

Card 1/4

Z/026/62/007/003/003/003
D407/D301

General solution ...

and S_{21}) is zero. The electromagnetic field in the region V_1, V_2 is generally expressed by superposition of individual vector functions of the electric or magnetic field intensity. The author formulates now the boundary conditions according to the common electromagnetic field theory and derives the linear current density (K) which will not be zero on the conducting coat S , and zero on the area S_{12} laying inside the no-loss dielectric. By calculating the intensities (H_1, H_2 and E_γ) of the magnetic field in the regions V_1, V_2 and the area S_{12} respectively, with the aid of the Huygens-Kottler formula, and mutual substitution, the author arrives at the expression $K(E_\gamma)$, where the contact area $S_{12} = S_{21}$ is the domain of definition of the linear operator $K(E_\gamma)$. The author proves then the symmetry of the operator, and determines the properties of the surface conduction-current functional $\Phi(E_\gamma) = \int_{S_{12}} (E_\gamma K(E_\gamma)) dS$. The

stationary state of this functional is given when

$$K(E_\gamma) = 0, \quad (9)$$

i.e. when the magnetic-field intensity in the region V_1 is an anal-

Card 2/4

General solution ...

Z/026/62/007/003/003/003
D407/D301

ytic continuation of the magnetic-field intensity in the region V_2 , whereby

$$\phi(E_\gamma) = 0. \quad (10)$$

The latter expression and the condition of the stationary state, are prerequisites for calculating the actual value E_γ , and used in this article to describe an electromagnetic field in a complex system. The accuracy of the calculation of the functional ϕ is determined according to a method called 'approximation degree according to energy' and described in Soviet literature. In this method, the approximation degree of function u to function v is generally defined by the expression

$$\int_{\Omega} (\langle u - v \rangle \cdot A(u - v)) d\Omega \quad (12)$$

where A is a linear operator with the domain of definition Ω , and u and v are two vectorial functional arguments of the operator A . However, a precision comparison is possible only between such methods which permit one to determine how the condition of the stationary state is fulfilled. Generally, it can be said, that the mere value of the functional ϕ is a sufficient accuracy criterion when methods are compared where electric-field intensities on the contact

Card 3/4

General solution ...

Z/026/62/007/003/003/003
D407/D301

area are expressed by the Fourier series (polynomials) with the same number of variables, but different coefficients. Best results are achieved with a method where the functional Φ assumes a minimum. The described method can also be expanded to a space composed of more sectional regions. There are 2 figures. *f*

ASSOCIATION: FTJF

SUBMITTED: May 15, 1961

Card 4/4

KVASIL, Bohumil, prof., dr.

A contribution for determining the phase velocity of propagation of electromagnetic waves in non-homogenous conductors. Aplikace mat 7 no.5:375-386 '62.

1. Fakulta technické a jaderné fyziky, Praha 1, Břehova 7.

L 23093-65 EWT(1)/EWT(m)/EPF(c)/EEC(f)/EWA(d)/EWP(t)/EEC(b)-2/EWP(b)

Pr-4 IJP(c) JD/JG/GG

ACCESSION NR: AP4047828

2/0002/64/000/004/0566/0570

AUTHOR: Kvasil, B. (Corresponding member CSAV)

TITLE: Superconducting materials. The properties of superconductors and their uses

SOURCE: Ceskoslovenska akademie ved. Vestnik, no. 4, 1964, 566-570

TOPIC TAGS: superconductivity, superconductor, liquid helium temperature, cryogenic equipment, helium liquefier, solid superconductor, superconductor magnet

ABSTRACT: This article reviews the properties of superconductors and their uses in industry and technology, the state of basic research in superconductors in the world, the state of worldwide applied superconductor research, and the state of basic and applied superconductor research in the CSR. The author points out that the theory of solid superconductors, the principal properties of which have been discovered in the last three years, has not yet been worked out. He concludes that superconductor research and the use of superconductors has lagged far behind in Czechoslovakia due principally to the fact that it has not been generally pos-

Card 1/3

L 23093-65

ACCESSION NR: AP4047828

sible in recent years to carry on experimentation at liquid-helium temperatures. The Kralovopolsky Machine-Building Plants, however, have begun the production of helium liquefiers which should rapidly correct this situation. In view of the great prospects for the utilization of superconductors in technology and research, increased attention will be given to this field in the future in Czechoslovakia. For the present it will be necessary to concentrate on the solution of the problem of "the investigation and development of superconductor magnets," because it is in this domain that the most effective use of superconductors may be expected in the years immediately ahead. Groups of scientific workers are being educated and trained to work on this problem. They will be able to follow world developments in superconductors and in case of need will form the nucleus of larger scientific groups to solve new and current problems. To achieve this goal it will be necessary: 1) to complete the construction of the experimental and scientific staff bases of the laboratories and institutes participating in the solution of the problem mentioned; 2) to send Czech workers for short study periods abroad beginning in 1964; and 3) to guarantee the refining of high-purity rare metals (Nb, Zr, V, Ta, Ti, and others). Until this problem is solved, the materials mentioned will continue to be imported. In view of the importance of the discovery of solid superconductors for magnetohydrodynamic research and for elec-

Card 2/3

L 23093-65

ACCESSION NR: AP4047828

2

trical engineering in general, and in the framework of major state problem K-II-6.1 (The Investigation of the Magnetohydrodynamic Transformation of Heat into Electricity), the Elektrotechnický ústav SAV, Bratislava (The Electrical Engineering Institute of the Slovak AS) in 1963 initiated research on the use of superconductors to generate powerful magnetic fields. In collaboration with this institute, the Československá komise pro atomovou energii (Czechoslovak Commission for Atomic Energy), took the first steps to organize research in solid superconductors in the CSR and made a number of decisions relating to arrangements for the production of helium liquefiers in Czechoslovakia, the equipping of Czechoslovak laboratories with cryogenic equipment, and cooperation with the USSR in the field of superconductor research.

ASSOCIATION: none

SUBMITTED: 00

ENCL: 00

SUB CODE: GP

NO REF SOV: 000

OTHER: 000

Card 3/3

KVASIL, J.

Scientific conference of the Higher School of Transportation
in Zilina. Slaboproudy obzor 24 no.12:734 D'63.

KVASIL, J.

KVASIL, J. N. D. Bosyl's Electric Filters; a book review. p. 398

Vol. 17, no. 7, July 1956

SLABOPROUDY OBZOR

TECHNOLOGY

Praha, Czechoslovakia

So: East European Accession Vol. 6, no. 2, 1957

KVASIL, J.

Ideal converter as a new instrument of analysis of electric circuits. p. 449.

SLABOPROUDY OBZOR. (Ministerstvo vseobecniho strojirenstvi, Ministerstvo, spoju a Ceskoslovenska vedecko-technicka spolecnost, sekce elektrotechnika) Praha, Czechoslovakia, Vol. 20, No. 7, July 1959.

Monthly List of East European Accessions (EEAI) LC, Vol. 8, No. 11, November 1959.

Uncl.

KVASIL, Josef, inz.

Analysis of cascade-connected active four-terminal networks of special kinds. Slaboproudy obzor 22 no.2:70-73 '61. (ERAI 10:5)

1. Vysoka skola dopravní.
(Electric networks)

KVASIL, J., inz.

"Theory and use of linear network" by G.Wunsch. Reviewed by
J.Kvasil. Slaboproudy obsor 23 no.11:Suppl.:Literatura 23
no.11:L85 '62.

KVASIL, Josef, inz.

"Circuit theory and design" by Dz. Stjuart [Stewart, J.L.].
Reviewed by Josef Kvasil. Slaboprouty obzor: Suppl. literatura
24 no.5: L35 '63.

KVASIL, Josef, inz.

"Principles of wire transmission engineering" by H.Schroder.
Reviewed by Josef Kvasil. Slaboproudý obzor 24 no.10:Suppl.:
Literatura 24 no.10:L77 '63.

KVASIL, L., inz.

"Theoretic basis of automation and telemechanics" by V.N. Lupal,
I.M. Bosin, S.A. Pereborov, V.A. Smirnova and A.A. Eiler. Reviewed
by J. Kvasil. Slaboproudy obzor 23 no.9: Suppl: Literatura 167, 169
'62.

KVASINKOV, E.I.; SUMNEVICH, M.G.

[Microbiological principles of the ensilage of fodder in
Uzbekistan] Mikrobiologicheskie osnovy silosovaniia kormov
v usloviakh Uzbekistana. Tashkent, Izd-vo Akad. nauk
UzSSR, 1953. 101 p. (MIRA 16:1)
(Ensilage)

USSR/Cultivated Plants - Fodders.

M

Abs Jour : Ref Zhur Biol., No 12, 1958, 53674

Author : Kvasinkov, V.V., Mukhortov, Ya.N., Kushilkina, N.V.,
Turbin, K.G.

Inst : Voronezh Institute of Agriculture

Title : The Effect of Sudan Grass on Soil Structure

Orig Pub : Vestn. s.-kh. nauki, 1957, No 4, 49-54

Abstract : Experiments conducted by the Voronezh Institute of Agriculture on leached out medium clayey chernozem in 1955-1956, showed that toward the end of vegetation Sudan grass had accumulated, in the soil layer of 0-40 cm, 37.9-44.1 centners/ha of air-dry roots, the mixture of Sudan grass with vetch, peas or vetchling accumulated 42.2-53.7 centners/ha, the mixture of alfalfa and couch grass of the first year of use accumulated 35.8-41.5

Card 1/3

- 68 -

USSR/Cultivated Plants - Fodders.

M

Abs Jour : Ref Zhur Biol., No 12, 1958, 53674

centners/ha. Mixtures of Sudan grass with legume cultures produced 30% more of thin roots (diameter < 1 mm) than the pure sowing of Sudan grass or the sowing of perennial grasses. Toward fall, 24% of the thin roots of the accumulated mixture of Sudan grass and vetchling underwent decomposition. With regard to the accumulation of water resistant soil aggregates, the total N content and the content of nitrates- the mixtures of Sudan grass with legume cultures were almost equal to the perennial grasses. The buckwheat yield on the mixture of Sudan grass and vetch comprised 13.6 centners/ha; on the Sudan grass the yield was 12.9 centners/ha; on the vetch-oat mixture 13.5 centners/ha and on the perennial grasses - 13.7 centners/ha. The hay yield of the mixture of Sudan grass with vetch comprised 43.4 centners/ha; the yield of Sudan grass was 40.4 centners/ha; the yield of vetch-oat mixture was 28.7 centners/ha and the yield of the

Card 2/3

TAVBERIDZE, I.D.; MIKADZE, I.I.; KVASKHVADZE, K.S.

Effective use of sodium humate in drilling [in Georgian with summary
in Russian]. Trudy Inst. khim. AN Gruz. SSR 13:137-144 '57.

(Sodium) (Oil well drilling fluids) (Humates) (MIRA 11:4)

TAVBERIDZE, I.D.; MIKADZE, I.I.; KVASHVAIDZE, K.S.

Preparation and use of emulsions of petroleum products from
self-emulsifying oil. Trudy Inst.khim.AN Gruz.SSR 16:159-166
'62. (MIRA 16:4)

(Petroleum products)

(Emulsions)

UKOLOVA, M.A.; KVASKINA, Ye.B. (Rostov-na-Donu)

Relation to the tumor process to thrombokinase activity in the
tumor tissue. Arkh.pat. 24 no.5:7-13 '62. (MIRA 15:5)
(THROMBOPLASTIC SUBSTANCES) (TUMORS)

MALAKHOVA, N.I.; PIZHIDAYEVA, L.F.; GORDIYCHUK, K.S.; KVASKO, N.Z.

Chemical processing of hornbeam wood for cellulose and
semicellulose. Bun. 1 der. prom. no.2:16-18 Ap-Je '64.
(MIRA 17:9)

TOPOL'NIK, N.K.; KVASKO, N.Z.; TSETZERO, S.V.

Modernizing the individual units of the papermaking machine
No. 1 at the Poninka Woodpulp and Paper Combine. Bum. i der.
prom. no.4:30-34 O-D '63. (MIRA 17:3)

GRINBERG, M.M.; KVASKO, N.Z.

Manufacture of writing paper using blanched reed cellulose.

Bum. 1 der. prom. no.3:32-34 J1-S '64.

(MIRA 17:11)

А. ВАСКОВ, А. И.

ZONNENBERG, S.M.; KVASKOV, A.I.

Machine tool manufacture and automatization of universal equipment
at the Kikhachev Automobile Plant. Stan.i instr. 28 no.11:34-35

N '57.

(MIRA 10:12)

(Machine tools)

(Automatic control)

L 41095-66 EWT(d)/EWT(1) /EWT(m)/EWP(k)/T/FSS-2/EWP(w)/EWP(f)/EWP(x)/EWP(t)/ETI

ACC NR: AP6027206

SOURCE CODE: UR/0193/66/000/006/0037/0038

IJR(c) TT/EM/WW/JD/JG/DI/JT
AUTHOR: Yalovega, N. V.; Kvaskov, A. N.

ORG: none*

TITLE: Electromagnetic flow meter for liquid metals ¹⁴

SOURCE: ²⁴Byulleten' tekhniko-ekonomicheskoy informatsii, no. 6, 1966, 37-38

TOPIC TAGS: flow meter, ~~electromagnetic flow meter~~, liquid metal, ~~liquid metal flow meter~~, liquid metal flow ²⁵ELECTROMAGNETISM

ABSTRACT: An electromagnetic flow meter for liquid metals has been developed at the Moscow Aviation Institute. The flow meter is intended for use in the alkali metal industry, metallurgical and power industry, and in various purpose hydraulic systems. The sensing elements of the meter never come into contact with the liquid metal. The meter is of simple design, is highly sensitive, and with some modification can be used in automatic control systems of power plants operating under widely varying thermal conditions. Orig. art. has: 1 figure. [DV]

SUB CODE: 13, 18, 14/ SUBM DATE: none/ ATD PRESS: 5055

Cord 1/1 hs

UDC: 681.121.082.7

L-38387-66 EWT(d)/EWT(l)/EWT(m)/EWP(w)/EWP(v)/T-2/EWP(t)/ETI/ETI(r) IJP(c) EN/WW/JD/JG

ACC NR: AP6024257

SOURCE CODE: UR/0193/66/000/005/0041/0042

AUTHOR: Yalovega, N. V.; Kvaskov, A. N.

ORG: none

TITLE: Asynchronous liquid metal pump

SOURCE: Byul tekhn-ekon inform, no. 5, 1966, 41-42

TOPIC TAGS: liquid metal pump, current carrier

ABSTRACT: A linear type of asynchronous liquid metal pump, developed by the Moscow Aviation Institute im. S. Ordzhonikidze, is briefly described. The pump has the main advantage of induction pumps, i.e., their contactless feature. In operation, the asynchronous pump does not differ from the conduction pump. However, the role of current carrying busbars is played here by the liquid metal. The accompanying figure shows a cross section of the pump. Linear channel 1 of the pump has a transverse, hermetic grommet 2 not in galvanic contact with the liquid metal. Its surface is coated with thermally insulating layer 3. Magnetic circuit of power transformer 4 passes through the grommet. The primary winding of transformer 5 is fed a-c voltage. Geometrical dimensions of the channel are chosen taking into account the density of the current flowing through the liquid metal. The

Card 1/2

UDC: 621.65 : 621.746.2

L 38387-66

ACC NR: AP6024257




Fig. 1. Cross section of the asynchronous pump

optimum coupling of parameters occurs when the transverse excitation current and the secondary current in the liquid metal are in phase. The main technical characteristics of the pump include: capacity, 2.3 l/sec; static pressure, 0.4 kg/cm; hydraulic efficiency, 10.4%; and weight, 10.5 kg. Orig. art. has: 1 figure. [JR]

SUB CODE: 13/ SUBM DATE: none/ ATD PRESS: 5042

Card 2/2/MLP

concentration and agglomeration of iron ores from the Bogoslovskii deposits (Ural) of the Kadeshinskii district. A. P. Knyazev. *Inst. Mekhanicheskoi Obrabotki Polym. (Inst. Mech. Treatment of Polym.)*. *Concn. and Agglomeration of Iron Ores in U. S. S. R.* 1932, 84-102. The following ores were investigated: (1) chromic Fe ores; (2) magnetic Fe ores, (a) high-grade S magnetites, (b) low-grade S magnetites; (3) fine-grained magnetites, (d) Cu-contg. magnetites; (3) fine-grained magnetites, (d) brown Fe ores. (4) contained red clay Fe ores; (5) FeO traces to 0.21, SiO₂ 19.20-44.78, Fe₂O₃ 37.0-55.4, MnO 0.11-0.97, CaO 1.18-1.36, MgO 0.20-0.53, P₂O₅ 0.29-1.46, S 0.048-0.065, Fe (total) 25.00-38.00, H₂O 0.84-1.43 and loss through heating 0.28-12.47%. The ore was classified by screening, washed, and electromagnetic concn. of the poorer classes was carried out. The highest concn. of Fe reached 48.50%. Good agglomeration was obtained by using an ore of 0-0 mm. grain, 7% coke and about 12% H₂O. (2) contained Fe (total) 37.2-43.8, FeO 10.55-12.55, S 0.37-0.78 and Cu 0.02-0.03%. The Fe was concd. after an electromagnetic sepn. up to 45.63-50.28%. The final chem. compn. of the concentrate was SiO₂ 6.68-10.80, Fe₂O₃ 57.50-63.76, FeO 20.40-22.95, Al₂O₃ 0.25-3.90, CaO 1.24-1.52, Mn none, MgO none, S 0.06-0.25, P₂O₅ 0.01-0.03, Fe (total) 50.5-60.4 and losses through heating 0.08-2.08%. In the screening of (a) the S is concd. in the breeze up to 2%; however, the S content cannot be lowered below 0.5% in the large pieces through addnl. concn. by electromagnetic sepn. The nonmagnetic fraction is an ore with 2-5% S and 45-60% Fe. In the agglomeration the S content can be lowered to 0.01-0.02% and in oxidizing roasting to 0.15-0.28%. In (b) the and in oxidizing roasting to 0.15-0.28%. In (b) the slightly magnetic Cu minerals were sepd. by magnetic separation and the Cu tailings were sepd. by magnetic flotation for the prepn. of Cu concentrates, yielding up to 33.32% Cu. (1) contained Fe (total) 35.15-44.2, magnetite ad. Fe 1.06-1.34, SiO₂ 23.57-30.08, Al₂O₃ 11.0-13.0, CaO 0.46-0.51, MnO 0.09-0.11, P₂O₅ 0.08-0.108, Cr₂O₃ 1.70-2.47, S 0.07-0.103 and loss on heat treating 6.41-8.76%. Up to 80-90% of Cr was sepd. by screening the ore and using the 2 mm. grain, concg. and sepg. by electromagnetic methods. The recovery of Fe amounted to 75.22%. A preliminary roasting of the ore raised the Fe rtn. to 84%. A. A. Bochtling

1ST AND 2ND ORDERS																										PROCESSING AND PROPERTIES INDEX																										3RD AND 4TH ORDERS																									
<p>Testing the concentrability of the iron ore from the Malo-Khinganaki deposit. A. P. Kyskuy. <i>Inst. Mekhanicheskoi Obrabotki Poreznykh Iskopnykh Mekhanizm (Inst. Mech. Treatment Ores). Concn. and Agglomeration of Iron Ores in U. S. S. R. 1032, 143-51.</i>—The ore contains SiO_2 44.87, Fe_2O_3 48.00, FeO 0.01, Al_2O_3 1.0, S 0.20, P_2O_5 0.21, MnO 0.37, CaO 0.23, MgO 0.05%; loss on heat treating is 1.8%. It consists of hematite and quartz. It was found that in a magnetic sepn. the concentrate would contain FeO 15.4, SiO_2 21.41, Al_2O_3 2.60, P_2O_5 0.20, S 0.41 and a total of Fe of 54.6%, while a flotation would yield correspondingly 0.32, 20.27, 1.58, 0.34, 0.35 and 60.4%. A. A. B.</p>																																																																													
<p>450-SLA DETAILING LITERATURE CLASSIFICATION</p>																																																																													

Ca

Testing the concentrability of the Dashkesan (Caucasus) iron ore. A. P. Kvaskov. *Inst. Mekhanicheskoi Obrabotki Poryadnitsa* (Institute of Mechanical Treatment Ores). *Concn. and Agglomeration of Iron Ores in U. S. S. R.* 1932, 152-60.—The ore, which is of the magnetite-garnet type, contains Fe 30.56-55.10, SiO₂ 0.40-17.60, Al₂O₃ 3.12-6.36, CaO 0.10-14.08, MgO 0.89-1.10, MnO 0.18-0.26, S 0.29-0.35, P₂O₅ 0.05-0.18, As 0.003-0.004, and the loss on heat treating is 0.44-0.22%. It is concluded that the concn. should be effected with an ore of 25-30 mm. grain size. A 56-59% concn. of Fe is obtained by eliminating the concentrates after the sepn. of the fine ore. A content of Fe reaching 61-63% is possible if the ore is ground to 2 mm. and the tailings are sepd. in the first stage of the process.

A. A. Bochtlingk

ASR-51A METALLURGICAL LITERATURE CLASSIFICATION

Technical sampling of iron ores from Siberian deposits for testing their concentratability. A. P. Kyskov. *Izv. Mekhanicheskoi Obrabotki Podelnuih Likspirmitkh Mekhanob. (Inst. Mech. Treatment Ores). Concn. and Agglomeration of Iron Ores in U. S. S. R. 1932, 188-192.* The geology of the Balbagar and Sosnovui Baltz deposits is discussed and the sampling procedure is described.

A. A. Boshiling

CIA-RDP86-00513R000928310012-5"

KVASKOV, A. P.

PA 43/43T84

USSR/Metals

Mar 1948

Iron

Magnetic Materials

"Preparations for Smelting Magnetic Iron Ore," A. P. Kvaskov, Candidate Tech Sci, UralMekhaNobr, 4 $\frac{1}{2}$ pp

"Stal'" No 3

Magnetic iron ore after proper dressing and agglomeration becomes high-quality dome-furnace raw material. As result of combined dressing, serves as base for smelting of pig for quality metallurgy. Output necessary for auxiliary dressing processes low and can be recovered to great degree by realization of secondary products (ore of nonferrous and rare metals).

43T84